

SPECIFICATIONS

		Vented Models		
		VFX2612E	VFX3024E	VFX3048E
Nominal DC Input Voltage		12 VDC	24 VDC	48VDC
Continuous Power Rating at 25° C		2600 VA	3000 VA	3000 VA
AC Voltage/Frequency		230 VAC 50 Hz	230 VAC 50 Hz	230 VAC 50 Hz
Continuous AC RMS Output at 25° C		11.3 amps AC	13.0 amps AC	13.0 amps AC
Idle Power	Full	≈ 20 Watts	≈ 20 Watts	≈ 23 Watts
	Search	6 Watts	6 Watts	6 Watts
Typical Efficiency		90%	92%	93%
Total Harmonic Distortion	Typical	2%	2%	2%
	Maximum	5%	5%	5%
Output Voltage Regulation		± 2%	± 2%	± 2%
Maximum Output Current	Peak	28 amps AC	35 amps AC	35 amps AC
	RMS	25 amps AC	25 amps AC	25 amps AC
AC Overload Capability	Surge	4600 VA	5750 VA	5750 VA
	5 Second	4000 VA	4800 VA	4800 VA
	30 Minutes	3100 VA	3300 VA	3300 VA
AC Input Current Maximum		30 amps AC	30 amps AC	30 amps AC
AC Input Voltage Range (MATE Adjustable)		160 to 300 VAC	160 to 300 VAC	160 to 300 VAC
AC Input Frequency Range		44 to 56 Hz	44 to 56 Hz	44 to 56 Hz
DC Input Voltage Range		10.5 to 17.0 VDC	21.0 to 34.0 VDC	42.0 to 68.0 VDC
Continuous Battery Charge Output		120 amps DC	85 amps DC	45 amps DC
Warranty		Standard 2 year / Optional 5 year		
Weight	Unit	54 lbs (25 kg)		
	Shipping	62.2 lbs (28 kg)		
Dimensions (H x W x L)	Unit	12 x 8.25 x 16.25" (30 x 21 x 41 cm)		
	Shipping	21.75 x 13 x 22" (55 x 33 x 56 cm)		